



R&K-ALM2527-3943-SMA



OUTLINE DRAWING

※ IN MILLIMETERS



TYPICAL PERFORMANCE (Temp @+25°C)

- Broadband Frequency : 2500 ~ 2700MHz
- Output Power : +43dBm
- Gain Flatness : ±1.0dB (typ.)
- Without Output circulator
- **Low Cost** : @¥198,000



SPECIFICATIONS

Frequency Range	: 2500~2700MHz
Small Signal Gain	: +39dB (typ.)
	: +38dB (min.)
Gain Flatness	: ±1.0dB (typ.)
Output Power@1dB Comp.	: +40dBm (min.)
Output I.C.P.	: +53dBm (typ.) @2600MHz
Noise Figure	: 11dB (max.)
Impedance	: 50Ω
Input VSWR	: 1.5 : 1 (typ.)
Output VSWR	: 3.0 : 1 (typ.)
DC Supply Input	: +12V ±0.5V
	: 9A (max.)
Maximum RF Input Power	: +7dBm
Operating Temperature	: -10°C to +45°C
Storage Temperature	: -15°C to +65°C
Connectors	: SMA-FEMALE
Weight	: 3kg (typ.)





Forced Air Cooling Required

HOW TO ORDER

Model Name
R&K-ALM2527-3943-SMA └ No Option



SCHEMATIC



R&K reserves the right to make changes in the specifications of or discontinue products at any time without notice. R&K products shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as aerospace uses or medical life support equipment. Further, R&K cannot export products to any country for use in military or defense applications.

R&K Company Limited

721-1 Maeda, Fuji-City, Shizuoka-Pref. 416-8577 Japan
 Tel : +81-545-31-2600 E-mail : info@rkco.jp
 Fax : +81-545-31-1600 URL : http://rk-microwave.com