


DOUBLE BALANCED MIXER




R&K-MDL560



OUTLINE DRAWING

※IN MILLIMETERS



- Frequency : DC-3000MHz
- Low LO Drive Level : +7dBm
- Low Cost / 8PIN Package
- RoHS Compliance

SPECIFICATIONS

Frequency Range [LO&RF] : 1-3000MHz
[IF] : DC-1000MHz
Conversion Loss (LO Drive Level +7dBm)

	1 - 100MHz	100 - 1000MHz	1000 - 3000MHz
Typ.	6.0dB	6.0dB	9.0dB
Max.	8.5dB	8.0dB	11.0dB

Isolation (min.)



	1 - 100MHz	100 - 1000MHz	1000 - 3000MHz
LO - RF	20dB	25dB	25dB
LO - IF	25dB	30dB	20dB
RF - IF	25dB	20dB	10dB

Input IP3 @Center Band : +15dBm (typ.)
Input 1dB Comp. Point : +7dBm (typ.)
Impedance (All Ports) : 50 Ω
Maximum RF Input Power : 100mW
Maximum Peak IF Current : 50mA
Operating Temperature : -40°C to +85°C
Storage Temperature : -40°C to +100°C




HOW TO ORDER

Model Name
R&K-MDL5608P 8P=8PIN Package

TYPICAL PERFORMANCE (Temp @+25°C)



SCHEMATIC



Function	Pin No.
RF	1
IF	3
LO	8
GND	2, 5, 6, 7
N.C.	4

R&K reserves the right to make changes in the specifications of or discontinue products at any time without notice. R&K products shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as aerospace uses or medical life support equipment. Further, R&K cannot export products to any country for use in military or defense applications.

R&K Company Limited

721-1 Maeda, Fuji-City, Shizuoka-Pref. 416-8577 Japan
Tel: +81-545-31-2600 E-mail: info@rkco.jp
Fax: +81-545-31-1600 URL: http://rk-microwave.com