R&K-MDM300



- Frequency :DC-5000MHz
- Mid LO Drive Level :+10dBm
- Small & Low Cost / Surface Mount
- RoHS Compliance

SPECIFICATIONS

Frequency Range [LO&RF] : 2000-5000MHz
[IF] : DC-2500MHz
Conversion Loss (LO Drive Level +10dBm)

	2000 - 3000MHz	3000 - 4000MHz	4000 - 5000MHz
Typ.	6.0dB	7.0dB	7.5dB
Max.	8.5dB	9.0dB	9.5dB

Isolation (min.)

	2000 - 3000MHz	3000 - 4000MHz	4000 - 5000MHz
LO - RF	15dB	15dB	20dB
LO - IF	10dB	5dB	10dB
RF - IF	5dB	5dB	10dB

Input IP3 @Center Band	: +15dBm (typ.)
Input 1dB Comp. Point	: + 3dBm (typ.)
Impedance (All Ports)	: 50Ω
Maximum RF Input Power	: 50mW
Maximum Peak IF Current	: 50mA
Operating Temperature	: −40℃ to + 85℃
Storage Temperature	: −40℃ to +100℃
Max.Reflow Soldering Temp.	: 260℃,10sec.
Reflow Soldering Repeatability	: 3 times
Weight (Standard)	: 0.3g (typ.)

OUTLINE DRAWING

※IN MILLIMETERS



HOW TO ORDER

Model Name
R&K-MDM300ST-BLK

- BLK=Antistatic bag
- TR2=Tape & Reel Package
- ST=Case Type of ST

TYPICAL PERFORMANCE (Temp @+25℃)

Conversion Loss



Conversion Loss vs LO Drive Level



SCHEMATIC



Isolation



Input IP3



Function	Pin No.
LO	1
RF	5
IF	7
GND	2,3,4,6,8

R&K reserves the right to make changes in the specifications of or discontinue products at any time without notice. R&K products shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as aerospace uses or medical life support equipment. Further, R&K cannot export products to any country for use in military or defense applications.

R&K Company Limited
721-1 Maeda,Fuji-City,Shizuoka-Pref.416-8577 Japan
Tel : +81-545-31-2600 E-mail : info@rkco.jp
Fax : +81-545-31-1600 URL : http://rk-microwave.com