


DOUBLE BALANCED MIXER




R&K-MDS060



OUTLINE DRAWING

※IN MILLIMETERS



- Frequency : DC-2200MHz
- S-High LO Drive Level : +20dBm
- Small & Low Cost / Surface Mount
- RoHS Compliance

SPECIFICATIONS

Frequency Range [LO&RF] : 800-2200MHz
 [IF] : DC-800MHz
 Conversion Loss (LO Drive Level +20dBm)

	800 - 1200MHz	1200 - 1800MHz	1800 - 2200MHz
Typ.	7.0dB	5.5dB	6.0dB
Max.	9.5dB	7.5dB	8.0dB

Isolation (min.)



	800 - 1200MHz	1200 - 1800MHz	1800 - 2200MHz
LO - RF	20dB	20dB	20dB
LO - IF	15dB	15dB	20dB
RF - IF	10dB	5dB	10dB

- Input IP3 @Center Band : +21dBm (typ.)
- Input 1dB Comp. Point : +15dBm (typ.)
- Impedance (All Ports) : 50Ω
- Maximum RF Input Power : 500mW
- Maximum Peak IF Current : 50mA
- Operating Temperature : -40°C to +85°C
- Storage Temperature : -40°C to +100°C
- Max.Reflow Soldering Temp. : 260°C, 10sec.
- Reflow Soldering Repeatability : 3 times
- Weight (Standard) : 0.46g (typ.)




HOW TO ORDER

Model Name
R&K-MDS060SC-BLK BLK=Antistatic bag
 TR1=Tape & Reel Package
 SC=Case Type of SC
 SD=Case Type of SD

TYPICAL PERFORMANCE (Temp @+25°C)



SCHEMATIC



Function	Pin No.
LO	1
RF	4
I F	5
GND	2, 3, 6

R&K reserves the right to make changes in the specifications of or discontinue products at any time without notice. R&K products shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as aerospace uses or medical life support equipment. Further, R&K cannot export products to any country for use in military or defense applications.

R&K Company Limited

721-1 Maeda, Fuji-City, Shizuoka-Pref. 416-8577 Japan
 Tel: +81-545-31-2600 E-mail: info@rk.co.jp
 Fax: +81-545-31-1600 URL: http://rk-microwave.com