


DOUBLE BALANCED MIXER




R&K-MDS600



OUTLINE DRAWING

※IN MILLIMETERS



- Frequency : DC-500MHz
- S-High LO Drive Level : +23dBm
- Low Cost / 8PIN Package
- RoHS Compliance

SPECIFICATIONS

Frequency Range [LO&RF] : 1-500MHz

[IF] : DC-500MHz

Conversion Loss (LO Drive Level +23dBm)

	1 - 50MHz	50 - 200MHz	200 - 500MHz
Typ.	7.0dB	7.0dB	7.0dB
Max.	9.5dB	9.0dB	9.0dB

Isolation (min.)

	1 - 50MHz	50 - 200MHz	200 - 500MHz
LO - RF	45dB	35dB	35dB
LO - IF	40dB	35dB	30dB
RF - IF	25dB	20dB	15dB

Input IP3 @Center Band : +26dBm (typ.)

Input 1dB Comp. Point : +16dBm (typ.)

Impedance (All Ports) : 50Ω

Maximum RF Input Power : 1000mW

Maximum Peak IF Current : 50mA

Operating Temperature : -40°C to + 85°C



Storage Temperature : -40°C to +100°C

HOW TO ORDER




Model Name

R&K-MDS6008P 8P=8PIN Package

TYPICAL PERFORMANCE (Temp @+25°C)



SCHEMATIC



Function	Pin No.
RF	1
IF	3, 4
LO	8
GND	2, 5, 6, 7

R&K reserves the right to make changes in the specifications of or discontinue products at any time without notice. R&K products shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as aerospace uses or medical life support equipment. Further, R&K cannot export products to any country for use in military or defense applications.

R&K Company Limited

721-1 Maeda, Fuji-City, Shizuoka-Pref. 416-8577 Japan
Tel : +81-545-31-2600 E-mail : info@rk.co.jp
Fax : +81-545-31-1600 URL : http://rk-microwave.com