

DC Series

Model Name	Frequency Range (MHz)	Insertion Loss (dB) max	Coupling (dB)	Coupling Flatness (dB)	Directivity (dB) min	VSWR max	Power Rating (W)	Page
DC010-0S	0.5- 200	0.6	20.0±1.0	±0.5	20	1.5	1	
DC020-0S	0.5- 200	0.6	25.0±1.0	±0.5	20	1.5	1	
DC030-0S	2- 500	1.3	14.5±1.0	±0.5	18	1.5	1	
DC040-0S	2- 500	1.3	20.0±1.0	±0.5	18	1.5	1	
DC050-0S	5-1000	2.0	15.0±1.0	±0.8	17	1.5	1	
DC060-0S	5-1000	2.0	20.0±1.0	±0.8	17	1.5	1	
DC070-0S	1- 200	1.0	30.0±1.5	±1.0	18	1.3	20	
DC080-0S	1- 100	1.0	30.0±1.5	±1.0	18	1.3	50	
DC310-0S	800-1000	0.3	20.0±1.5	±0.5	20	1.2	100	
DC320-0S	1700-2000	0.5	20.0±2.0	±1.0	15	1.2	80	
DC330-0S	2000-2300	0.5	20.0±2.0	±1.0	15	1.3	60	
DC510-0S	700-3800	0.5	20.0±1.5	±1.0	18	1.3	120	
DC520-0S	1500-4500	0.5	20.0±1.5	±1.0	18	1.5	120	

R&K reserves the right to make changes in the specifications of or discontinue products at any time without notice. R&K products shall not be used for or in connection with equipment that requires an extremely high level of reliability and safety such as aerospace uses or medical life support equipment. Further, R&K cannot export products to any country for use in military or defense applications.

R&K Company Limited

721-1 Maeda, Fuji-City, Shizuoka-Pref. 416-8577 Japan
 Tel : +81-545-31-2600 E-mail : info@rkco.jp
 Fax : +81-545-31-1600 URL : <http://rk-microwave.com>